



型式 TYPE	伝熱面積 HEAT TRANSFER AREA	A	B	C	Dφ	E	F	H	N-Hφ	重量 WEIGHT
HCR-KT-40	0.25 m ²	1000	900	50	48.6	40A	20A	49	4-19	5.5 kg
HCR-KT-50	0.47	1000	890	55	60.5	50A	25A	59	4-19	7.0
HCR-KT-65	0.9	1000	880	60	76.3	65A	32A	70	4-19	11.0
HCR-KT-80	1.38	1000	870	65	89.1	80A	40A	78	8-19	13.0
HCR-KT-100	2.2	1000	860	70	114.3	100A	50A	95	8-19	17.0
HCR-KT-125	3.5	1000	860	70	139.8	125A	50A	110	8-23	24.0
HCR-KT-150	5.0	1000	830	85	165.2	150A	65A	127	8-23	32.0
HCR-KT-200	8.8	1000	800	100	216.3	200A	80A	150	12-23	67.0

5	ノズルソケット NOZZLE SOCKET	SUS304	2	
4	バッフル BUFFLE	SUS304	5	
3	チューブ TUBE	TITAN		
2	シェル SHELL	SUS304	1	
1	ノズルフランジ NOZZLE FLANGE	SUS329J4L	2	
品番 ITEM	部品名称 NAME	材質 MATERIALS	数量 QTY	備考 REMARKS

HCR-KT

図面番号
DWG.No.
REFERENCE DRAWING

株式会社
ZENSHIN CO.,LTD
JAPAN